




T815-21ER45 17 230 4x4.1/55T



### T815-21ER45 17 230 4x4.1/55T

The ARMAX 4x4 chassis is heavy-duty vehicle designated for hard terrain, difficult climatic and environment conditions. Cargo/Troop Carrier on TATRA T815-21ER45 17 230 4x4.1/55T Chassis is designed to carry troops or different loads to operate on roads, forest and field roads, off-road and/or to tow trailers up to 25 tons.

## TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS				
DIMENSION			STEERING	
Width		2 550 mm	L.H. compact steering	
Track	- front	2 034 mm		
	- rear	2 034 mm	FRONTAXLE	
Clearance		365 mm	Steered, driven with swinging half-axles, disengage- able drive, differential. Torsion bars and telescopic	
WEIGHT			shock absorbers	
Kerb weight		10 000 kg		
Payload		7 000 kg	REAR AXLE  Driven, with swinging half-axles, axle differential. Air bellows and coil springs plus telescopic shock absorbers	
GVW		17 000 kg		
Articulated vehicle max.permissible weight		42 000 kg		
Front axle max. permissible load		8 000 kg		
Rear axle max. permissible load		9 000 kg	TYRES, DISCS	
•		J	Tyres	14,00R20TL
FEATURES			Discs	10,00-20V
Climbing capacity at 17 000 kg		100 %		
Climbing capacity at 42 500 kg		30%	BRAKES	
Top speed		90 km.hod <sup>-1</sup>	Four separate brake systems: operational, emergency, parking and relief brake	
Turning circle diameter (outside)		$20,0 \pm 1,0 \mathrm{m}$		
Fording capability	,	1200 mm		
Crossing abillity - trench width		900 mm	CABIN Forward tilting, a manhole, dependent oil heater. Two	
Crusing range - on road approx		850 km		

#### **ENGINE**

Type TATRAT3B-928-10 EURO I

Nos. of cylinders

8

Bore/stroke

120/140 mm

Swept volume

12667 cm³

Power (netto)

230 kW /2 000 min¹

Torque (netto)

1300 Nm/1200 min¹

#### **CLUTCH**

Type TATRAMFZ 1x430, single-plate

### **GEARBOX**

Type TATRA 10 TS 140 synchromeshed nos. of forward gears 10 reverse 2

### **AUXILIARY GEARBOX**

Type TATRA 2,30 TR 1,6/2,6 downward, two-speed

# **ELECTRIC EQUIPMENT**

Circuit voltage 24V, minus pole grounded
Battery 165 Ah
Generator 28 V/ 55A
Startermotor 24 V/6,6 kW

# **FUEL TANK**

220 litres

seats.

### **BASIC EQUIPMENT**

Trailer drawbar.

Platform flatbed with tarpaulin, foldable benches rolled up sides of tarp, acces through the rear.